

APPA A17R Clamp Multimeter

Leakage Current Clamp Meter



- 6,000 Count digital large scale display Analog Bar graph
- AC 100.0 Amps capability
- AC 0.001mA Resolution
- True RMS reading (A17R only)
- Auto Ranging
- Auto Hold
- Data Hold
- Peak Hold
- Comparator
- Low Pass Filter with high stability
- Auto Power Off (Disable)
- Up to 40mm dia. (750MCM) Conductor Size 4 feet Drop Proof
- Deluxe Carrying Case
- Hand Guard & Stream Line Designed Convenient Battery Door
- CAT. III 300V Safety Standard

Specifications: (All at 23°C±5°C 80%RH)

ACA:	Ranges	6.000mA/60.00mA/600mA/6A/60A/100A
	Basic Accuracy:	±(1.0%+3d)
	Resolution	0.001mA

General

Sampling Rate:	5 times/sec
Overload Indication:	"OL"
Low Battery Indication	☐
Auto Power Off:	Approx. 20 minutes
Operating Temperature:	0°C~50°C
Storage Temperature:	-20°C~60°C
Temperature Coefficient:	0.2 x (Spec. Accuracy)/ °C, <18°C, >28°C Maximum
Conductor Size:	Up to 40 mm dia. (750MCM) Conductor Size Maximum
Maximum Jaw Opening	Up to 43mm
Safety:	IEC 61010 CAT III 300V and designed to meet UL61010 specifications
Battery Life:	60 hours (ALKALINE)
Power Requirement:	1.5V x 2pcs AAA Size batteries (IEC LR03)
Dimensions:	978mm(W) x 203mm(L) x 42mm(D)
Weight:	Approx. 300g
Accessories	Carrying Case, Alkaline battery (installed) and manual