

APPA SFlex-18D/18T

Flexible Current Probe Meter



APPA SFLEX-18D

- 3000A AC Current measurement
- 3000 count large scale LCD display with backlit
- Auto Ranging
- Data Hold
- 18inch head cable length
- 7.5mm coil diameter for tight space measurement
- Low Batt. Segment indicator
- Ergonomically designed one hand operation
- CAT IV 600V/ CATIII 1000V safety standard



APPA SFLEX-18T

- 3000A AC Current measurement
- Slide switch to change range
- Voltage output to universal voltage meters
- 18inch head cable length
- 7.5mm coil diameter for tight space measurement
- Low Batt. LED indicator
- Ergonomically designed one hand operation
- CAT IV 600V/ CATIII 1000V safety standard

Features

	APPA SFlex D	APPA SFlex T
Display	3000 count N/A	N/A
AC Current	0.01A-3000A	0.01A-3000A
Basic Accuracy: at 45 - 500Hz	±(3.0%+5d)	±3% of full scale
Auto Ranging	■	N/A
Measuring Method	TRUE RMS	TRUE RMS
Display Hold	HOLD	N/A
Backlit	■	N/A
Head Cable Length	18 inch	18 inch
Extension Cable Length	N/A	2 meter
Hand Guard Designed	■	■

General

	APPA SFlex D	APPA SFlex T
Overload Indication	"OL"	N/A
Low Battery Indication	□	LED
Auto Power Off: Approx. 20 minutes	■	N/A
Operating Temperature: 0°C-50°C, 80% RH	■	■
Storage Temperature: 20°C - 60°C	■	■
Temperature Coefficient: 0.2(Spec. Acc)/°C, <18°C or>28°C	■	■
Safety: IEC 61010 and designed to meet UL61010 specifications	CAT IV 600V CAT III 1000V	CAT IV 600V CAT III 1000V
Maximum Conductor Size	18" coil size	18" coil size
Coil Diameter	7.5mm	7.5mm
Power Requirement: IEC LR03, AM4 or AAA size Battery x 2	■	■
Battery Life: In hours (ALKALINE Battery)	200	160
Size: 350mm(L) x 130mm(W) x 25mm(H)(18" coil size)	■	■
Weight: In grams	200	200
Included with instrument: Battery and User manual	■	■