

ORDERING INFORMATION

CODE	DESCRIPTION	PRODUCT NUMBER	CARTON QTY.	WEIGHT (NET/ GROSS)
I 1283	Ledfire Lite Surface Mounted Emergency Luminaire	9336462 I 12830	4	-

OPERATIONAL INFORMATION

GENERAL				BATTERY	
Voltage	~230V	Emergency Classification	D40	Battery Type	LiFePO4
Frequency	50 Hz	Mounting Type	Surface / rod mount	Battery Voltage	6.4 V
Max. Ambient Temp.	40°C	Wiring	Hardwired	Battery Code(s)	I302
Class	2	Lamp Power	2.7W (D40)	Charging Time	16 Hours
Duration	90 / 120 min	Avg. Circuit Power	0.45 W	Charger Type	Variable
IP Rating	IP20	Max. Circuit Power	2.5 W		

CONSTRUCTION AND DIMENSIONS

BODY PC

NOTE: For more information on the chemical resistance of our polycarbonate, please see the technical downloads page on the Ektor website.

ACCESSORIES AND SPARE PARTS

CODE	DESCRIPTION
01302	Battery 1500mAH 2 Cell LiFePO4

SPACING TABLE (DISTANCE BETWEEN FITTINGS)

LUX	CLASSIFICATION	MOUNTING HEIGHT (M)															
		2.1	2.4	2.7	3	3.3	3.6	4	4.5	5	6	7	8	9	10	15	20
0.2	D40	16.7	17.4	18.0	18.6	19.1	19.6	20.1	20.8	21.3	22.1	22.7	23.0	23.1	23.1	19.4	
0.5	D40	12.0	12.5	12.9	13.2	13.5	13.8	14.0	14.3	14.5	14.5	14.3	13.7	12.8	11.4		
1	D40	9.3	9.6	9.8	10.0	10.1	10.2	10.3	10.2	10.1	9.4	8.2	4.8				

Datasheet is subject to change without notice

Last updated: **27 April 2016**