

PRODUCT UPDATE



LIFESAVER



LIFESAVER SERIES 2

SMOKE ALARM

The PSA LIFESAVER Series 2 smoke alarms are available in 2 models. The PSA LIFESAVER Model LIF5800/2 operates on a 240VAC power source with a 9VDC battery backup. The PSA LIFESAVER Model LIF5800RL/2 is 240VAC mains powered with a sealed rechargeable lithium battery backup.

Both models use photoelectric sensing technology. Photoelectric sensing alarms may detect visible particles (associated with smoldering fires) sooner than ionisation alarms.

The LIFESAVER Series 2 smoke alarms uses the popular QUICK SLIDE base plate design for user friendly and easy installation. It is compatible with Series 1 models.


The LIFESAVER Series 2 is AS3786:2014 approved and SAI Global Listed with a 5-year warranty.

FEATURES:

- Mains power hard-wired smoke alarm 240VAC with 9VDC battery backup (Model LIF5800/2)
- 240VAC with sealed rechargeable lithium battery backup designed to last for 10 years (LIF5800RL/2)
- Photoelectric Sensing Technology
- Insect screen over the smoke sensor
- Single button operation (Test and Hush feature)
- Surface mount QUICK SLIDE mounting base plate.
- Compatible to Series 1 smoke alarms.
- Stand alone operation or interconnect up to 24 units
- Tamper resistant feature
- Low battery warning delay. Silence low battery beeping for 8 hours
- First to alarm memory indication
- Chamber monitoring for maintenance
- Low power consumption 10mA
- Increase resilience to electrical interferences
- 5 Year warranty
- Approved to AS3786:2014 standard.

NEW FEATURE

Low battery warning delay. Silence low battery beeping for 8 hours. Giving you time to change the battery.



Tested and Complies to AS3786:2014 Standard.